



SMART AND SEXY. THAT WORKS.

THE NEW GENIUS^{MT} AND THE NEW MULTIMAX



WELCOME TO THE FAMILY

It's time to make the good even better!

The new generation of our GENIUS^{MT} and MULTIMAX combines the best of design and technology. The clear design language, the user-oriented operation, and the consistent further development of our technology create a new experience in cooking and baking.

Added value on every corner.

The new Family design. Inspired by the JOKER, clear lines and a timeless design transferred to GENIUS^{MT} and MULTIMAX. And as beauty also comes from the inside, we have optimized under the hood as well. The result: evolution in all areas.



USER FOCUS

Users are different. Our operation is simple - for everyone.



SUSTAINABILITY

Less consumption and even better results. That's economy that pays off!



CAPACITY

More inside does not have to be bigger. But more well thought



PERFORMANCE

On demand at any time and always in top condition. A team player for every situation.



FLEXIBILITY

A standard with many options. Individuality that makes sense.

DEVELOPMENT BY EXPERIENCE - THAT IS WHAT THE
NEW GENERATION OF ELOMA UNITS STANDS FOR.



DO YOU WANT A LITTLE MORE? THAT'S NEW.

VARIO-HANGING RACK

More than the standard. The vario hanging rack.¹ The standard from now on is flexibility. More space is simply not feasible.



9" DISPLAY

Catches the eye. The new 9-inch display. For big thumbs and small fingers. Anyone can operate this.



INDIVIDUALIZATION OF SOFTWARE

One for all needs. Individual software settings. For every user. Now with even more settings options.



ECO-STEAM

When less is more. Save water with Eco-Steam.² For the environment. And for a better cooking result.



POWER-STEAM

Full speed ahead. Power-Steam makes it possible. For all foods that really need steam.



LED AND DOUBLE GLAZING

Comfort in a twin pack. LED lighting and double glazing. Quite bright. Optionally, we add another pane on top.



autoclean PRO®

At ease with itself. autoclean PRO® for the GENIUS^{MT}.³ Off to after work. At the push of a button.⁴



¹ Up to 50% more capacity depending on rack and accessories.

² Eco-Steam saves up to 33% water compared to the steam function of the previous version.

³ With autoclean PRO®, there is a potential saving of 32% in water and chemicals compared to autoclean^{MT}.

⁴ Automatic cleaning when using the liquid cleaner.

STANDARD EQUIPMENT GENIUS^{MT} (SELECTION)



GENIUS^{MT} 6-11



GENIUS^{MT} 10-11

- 12 operating modes
- ADC — Active dehumidification control in 5 levels
- Automatic DST (Daylight Saving Time)
- Automatic resting time in accordance to humidity setting
- Automated cleaning and maintenance instructions, incl. Locking
- Glas control panel with 9" display and MultiTouch
- Manual steaming (additional)
- Pre-set of steam injection (in 10 ml steps)
- Blinking light following the program end
- Data and HACCP logging and display
- E/2 -Energy saving function
- Eco-Steam
- Start screen setting
- Favourites marking during saving
- Favourites list and favourites search
- Humidity setting: 0% - 100% (exact percentage)
- Fresh steam system
- Cooking time compensation (Multi Cooking PRO/ Multi Baking PRO)
- Additional cooking / baking time
- Individualisation of operating concept with password manager
- Integrated spray hose
- Core temperature, adjustable between 20°C and 100°C (to the exact degree)
- LAN interface
- Fan wheel autoreverse
- Fan wheel pulsed
- Multi-point core temperature sensor
- Language setting in 25 languages
- Multi-Eco-System: heat recovery
- Multi menu
- MT-Technology: baking mode
- Last[®] 20
- Multi Cooking PRO / Multi Baking PRO
- MultiTouch-Display
- Quick Mode cooking/baking
- Quick Mode cleaning
- Quick Set

- Power-Steam
- Program and media manager
- Program list with 1000 programs, 20 steps each
- Cleaning fully automatic: autoclean[®] PRO
- Preset of steam injection in ml or sec steps
- Special programs (low temperature cooking, regenerating, holding, defrosting, rising)
- SPS – Steam Protection System
- Start-Up settings
- Steptronic and step overview
- Temperature setting between 30°C and 300°C (to the exact degree)
- Timer function: starting and ending time
- Door left hinged
- Door with LED lighting and double glazing
- Quick release door lock
- Weekly programming PRO for cooking / baking programs and autoclean[®] PRO

OPTIONAL:

- Backmaster Edition (BME)
- Interface energy optimisation
- External core temperature sensor (also for BME)
- External sous-vide sensor (not for BME)
- Special voltage requirement
- Electrical door lock (for automatic release after cooking / baking / cleaning programs)
- Safety door lock
- Door with LED lighting and triple glazing
- WLAN

ELECTRIC

Connected load	11 kW
Voltage	400 V 3N AC
Protection	3 x 16 Amp
Weight	122 kg
Dimensions (W/D/H) in mm	925/805/840 mm

GAS

Connected load	12 kW
Voltage	230 V 1N AC
Protection	1 x 16 Amp
Weight	132 kg
Dimensions (W/D/H) in mm	925/805/840 mm

EXAMPLES / SELECTION OF DEVICES (OPTIONS)

ELECTRIC / AC PRO* LIQUID CLEANER

RH, LED/double glazing	EL6113801-3A
LH, LED/double glazing	EL6113901-3A

ELECTRIC / AC PRO* SOLID CLEANER

RH, LED/double glazing	EL6113802-3A
LH, LED/double glazing	EL6113902-3A

GAS / AC PRO* LIQUID CLEANER

RH, LED/double glazing	EL6116801-3A
------------------------	--------------

GAS / AC PRO* SOLID CLEANER

RH, LED/double glazing	EL6116802-3A
------------------------	--------------

BACKMASTER EDITION

ELECTRIC / AC PRO* LIQUID CLEANER

RH, LED/double glazing	EL6113807-3A
LH, LED/double glazing	EL6113907-3A

ELECTRIC / AC PRO* SOLID CLEANER

RH, LED/double glazing	EL6113808-3A
LH, LED/double glazing	EL6113908-3A

* AC PRO = autoclean[®] PRO

Further options and equipment can be found in the price list. All units are also available with LED / triple glazing. Gas units optionally available as natural gas H/L or liquid gas version. The Backmaster Edition is only possible with electric connection. No core temperature sensor is included as standard; this can be retrofitted externally at any time.

ELECTRIC

Connected load	17 kW
Voltage	400 V 3N AC
Protection	3 x 25 Amp
Weight	156 kg
Dimensions (W/D/H) in mm	925/805/1120 mm

GAS

Connected load	20 kW
Voltage	230 V 1N AC
Protection	1 x 16 Amp
Weight	166 kg
Dimensions (W/D/H) in mm	925/805/1120 mm

ELECTRIC / AC PRO* LIQUID CLEANER

RH, LED/double glazing	EL1113801-3A
LH, LED/double glazing	EL1113901-3A

ELECTRIC / AC PRO* SOLID CLEANER

RH, LED/double glazing	EL1113802-3A
LH, LED/double glazing	EL1113902-3A

GAS / AC PRO* LIQUID CLEANER

RH, LED/double glazing	EL1116801-3A
------------------------	--------------

GAS / AC PRO* SOLID CLEANER

RH, LED/double glazing	EL1116802-3A
------------------------	--------------

BACKMASTER EDITION

ELECTRIC / AC PRO* LIQUID CLEANER

RH, LED/double glazing	EL1113807-3A
LH, LED/double glazing	EL1113907-3A

ELECTRIC / AC PRO* SOLID CLEANER

RH, LED/double glazing	EL1113808-3A
LH, LED/double glazing	EL1113908-3A

DO YOU WANT A LITTLE MORE? THAT'S NEW.

VARIO-HANGING RACK

More than the standard. The vario hanging rack.¹ The standard from now on is flexibility. More space is simply not feasible.



ECO-STEAM

When less is more. Save water with Eco-Steam.² For the environment. And for a better cooking result.



POWER-STEAM

Full speed ahead. Power-Steam makes it possible. For all foods that really need steam.



LED AND DOUBLE GLAZING

Comfort in a twin pack. LED lighting and double glazing. Quite bright. And clear view inside.



autoclean PRO®

At ease with itself. autoclean PRO® for the MULTIMAX.³ Off to after work. At the push of a button.⁴



¹ Up to 50% more capacity depending on rack and accessories.

² Eco-Steam saves up to 33% water compared to the steam function of the previous version.

³ With autoclean PRO®, there is a potential saving of 32% in water and chemicals compared to autoclean^{MT}.

⁴ Automatic cleaning when using the liquid cleaner.

STANDARD EQUIPMENT MULTIMAX (SELECTION)

- 8 operating modes
- ADC — Active dehumidification
- Display actual / target temperature
- Automated cleaning and maintenance instructions
- Control panel with touchscreen and push-dial
- Manual steaming (additional)
- Cool-Down function: Manual-Temp adjustable
- Cool-Down function: Auto-Temp (Default settings)
- Data and HACCP logging and display
- E/2 -Energy saving function
- Eco-Steam
- Input numeric
- Humidity setting: 0% - 100% (in steps of 5% and 10%)
- Fresh steam system
- Cooking chamber: Seamless, hygienic cooking chamber
- Instruction: clean air filter
- Integrated spray hose
- Fan speed in 5 levels
- Fan wheel autoreverse
- Fan wheel pulsed
- Multi-point core temperature sensor
- Power-Steam
- Program list alphabetical
- Program list with 99 programs, 9 steps each
- Cleaning semi-automatic
- Acoustic signal adjustable
- Special programs (low temperature cooking, regenerating)
- SPS - Steam Protection System
- Standby after cleaning and 15 min. inactivity
- Stackable (Modular Solutions)
- Door seal, pluggable, for easy cleaning and maintenance
- Steptronic and step overview
- IP X5 water resistance
- Sound manager
- Temperature setting between 30°C and 300°C (to the exact degree)
- Entry of starting time up to 24 hours
- Selectable drying phase (only with AC PRO)
- Door left hinged
- Door with LED lighting and double glazing
- Door latching position 90°
- Quick release door lock

- Interface USB
 - Preheat function with default preheat temperature, adjustable
 - Entry of starting time up to 24 hours
- OPTIONAL:**
- Interface energy optimisation
 - External core temperature sensor (also for BME)
 - LAN interface
 - Multi-Eco-System: heat recovery
 - autoclean* PRO
 - Special voltage requirement
 - Safety door lock
 - WLAN



MULTIMAX 6-11

ELECTRIC	
Connected load	11 kW
Voltage	400 V 3N AC
Protection	3 x 16 Amp
Weight	122 kg
Dimensions (W/D/H) in mm	925/805/840 mm

GAS	
Connected load	12 kW
Voltage	230 V 1N AC
Protection	1 x 16 Amp
Weight	132 kg
Dimensions (W/D/H) in mm	925/805/840 mm

SELECTION OF DEVICES

ELECTRIC / AC PRO* LIQUID CLEANER	Art.-Nr.
RH, LED/double glazing	EL6103803-3A
RH, LED/double glazing, M-E-S**	EL6103805-3A
LH, LED/double glazing	EL6103903-3A
LH, LED/double glazing, M-E-S**	EL6103905-3A

ELECTRIC / AC PRO* SOLID CLEANER	
RH, LED/double glazing	EL6103804-3A
RH, LED/double glazing, M-E-S**	EL6103806-3A
LH, LED/double glazing	EL6103904-3A
LH, LED/double glazing, M-E-S**	EL6103906-3A

GAS / AC PRO* LIQUID CLEANER	
RH, LED/double glazing	EL6106803-3A
RH, LED/double glazing, M-E-S**	EL6106805-3A

GAS / AC PRO* SOLID CLEANER	
RH, LED/double glazing	EL6106804-3A
RH, LED/double glazing, M-E-S**	EL6106806-3A

WITHOUT AC PRO*	
Electric, RH, LED/double glazing	EL6103801-3A
Electric, LH, LED/double glazing	EL6103901-3A
Gas, RH, LED/double glazing	EL6106801-3A



MULTIMAX 10-11

ELECTRIC	
Connected load	17 kW
Voltage	400 V 3N AC
Protection	3 x 25 Amp
Weight	156 kg
Dimensions (W/D/H) in mm	925/805/1120 mm

GAS	
Connected load	20 kW
Voltage	230 V 1N AC
Protection	1 x 16 Amp
Weight	166 kg
Dimensions (W/D/H) in mm	925/805/1120 mm

ELECTRIC / AC PRO* LIQUID CLEANER	Art.-Nr.
RH, LED/double glazing	EL1103803-3A
RH, LED/double glazing, M-E-S**	EL1103805-3A
LH, LED/double glazing	EL1103903-3A
LH, LED/double glazing, M-E-S**	EL1103905-3A

ELECTRIC / AC PRO* SOLID CLEANER	
RH, LED/double glazing	EL1103804-3A
RH, LED/double glazing, M-E-S**	EL1103806-3A
LH, LED/double glazing	EL1103904-3A
LH, LED/double glazing, M-E-S**	EL1103906-3A

GAS / AC PRO* LIQUID CLEANER	
RH, LED/double glazing	EL1106803-3A
RH, LED/double glazing, M-E-S**	EL1106805-3A

GAS / AC PRO* SOLID CLEANER	
RH, LED/double glazing	EL1106804-3A
RH, LED/double glazing, M-E-S**	EL1106806-3A

WITHOUT AC PRO*	
Electric, RH, LED/double glazing	EL1103801-3A
Electric, LH, LED/double glazing	EL1103901-3A
Gas, RH, LED/double glazing	EL1106801-3A

* AC PRO = autoclean * PRO
 ** M-E-S = Multi-Eco-System

SMART AND SEXY. THAT WORKS.



Eloma GmbH • Otto-Hahn-Str. 10 • 82216 Maisach/Germany
T. +49 8141 395-0 • F. +49 8141 395-130 • sales@eloma.com
eloma.com

an Ali Group Company



The Spirit of Excellence