



## GASTRO K 1807 CSG A DL/2D/3D L2

With an energy consumption of 949 kWh/year (Energy test Ecodesign) the GASTRO K 1807 counter ranks in energy class C according to new EU legislation that will be introduced 1st July 2016.

The Ecodesign test method records the 24 hour energy consumption and multiplies it by 365 to get the annual energy consumption (AEC). The 24 hour consumption is calculated from 2 test periods of 12 hours each. The first period has sequences of door openings while the second is a stabilization period with closed door.

Equipped with stainless steel solidtop, 1 door section with 2 stainless wire drawers and 2 drawer sections, one with 2 x 1/2 drawers and one with 3 x 1/3 drawers.

GASTRO 07 range comprises of 1/1 GN, available with 2, 3 or 4 sections. Flat worktop or saladette worktop. Doors or drawers, with or without lock. Standard refrigeration (+2/+12°C), extended refrigeration (-5/+12°C) or freezing (-25/-5°C).

Available with electronic elevation and prepared for remote compressor.

## TECHNICAL INFORMATION

Varenummer	861800620
Category	Storage Counters
Type	Refrigerated counter
Line	Reach-in counter, 1/1 GN
Series	GRAM GASTRO 07
Equipped with	Stainless steel solid top, 1 door section with 2 stainless shelves and 2 drawer sections with 2 x 1/2 drawers and 3 x 1/3 drawers
Temperature range	+2/+12°C
Volume, gross	506 ltr.
Net usable volume	249 ltr.
Exterior/Interior	Stainless/Stainless
Dim. W x D x H, mm	1726 x 700 x 885/950 mm
Weight, packed	158 kg
Insulation	50 mm (cyclopentan)
Refrigerant / GWP	R 290 (propane)/0.07 kg/CO2e 0.23 kg/3
Ref.capacity at -10°	386 Watt
Connection	230 V, 50 Hz
Connection load	310 Watt
Energy Efficiency Class	D
Energy consumption / year (AEC)	1455 kWh

