

KPS 42 SH R



KPS 42 SH R, compatible with Rational oven, is a blast chiller/freezer featuring innovative technological solutions offering high food safety and performance. And with the new intuitive controller it has never been easier to manage chilling and freezing cycles.

Featuring

- Compatible with Rational type SCC 101
- Self closing door
- Removable support for 1/1 GN and 40 x 60 cm,
- Multipoint probe with 3 measuring points,
- Choose either the IFR operation, time or temperature controlled chill/freeze cycle.
- Prevent surface freezing damage with the IFR blast chilling function.
- Up to 20 customized cycles can be stored.
- HACCP alarms
- Operates as a storage cabinet after the chilling/freezing process has finished.

Height: 1850mm

Exterior / interior: Stainless / Stainless

Temperature range: -25 ° C / + 10 ° C.

Cooling capacity: 45 kg from + 70 ° C to + 3 ° C in 90 minutes.

Freezing capacity: 27 kg from + 70 ° C to -18 ° C in 4 hours

TECHNICAL INFORMATION

Varenummer	865789960
Category	Blast Chilling
Type	Blast Chiller/Freezer
Line	For 1/1 GN and 40x60 cm
Series	GRAM PROCESS
Equipped with	Right hand hinged reversible door, automatic door closing, removable support for 10 x 1/1 GN trays or bakery trays 60 x 40 cm, multipoint probe with 3 measuring points, HACCP alarms, LCD control panel + encoder for navigation
Compatible with	Rational type SCC 101
Temperature range	-25/+10°C
Exterior/Interior	Stainless/Stainless
Dim. W x D x H, mm	800 x 830 x 1850 mm
Weight, packed	200 kg
Insulation	75 mm (cyclopentane)
Climate class	4
Refrigerant / GWP	R 404 A/2.00 kg/CO2e 7844.00 kg/3922
Ref.capacity at -25°	2345 Watt
Connection / Connection load	400 V, 3N-/50 Hz / 3500 Watt
Chilling capacity	45 kg from +70°C to +3°C in 90 min.
Freezing capacity	27 kg from +70°C to -18°C in 4 hours
Sound level	72 dB(A)
Please observe	This model is available as a single phase unit. 230 V, 50 Hz - 30 amp fuse

