

U/KP 82 CCG L2 4S



Dual temperature cabinet with 2 compressor systems.
Extended temperature range from -25/+10°C (U) in the upper refrigerated section and quick-chill (KP) -30/+20°C in the bottom refrigerated section .

Equipped with: Right hand hinged reversible doors with lock, automatic door closing, 4 stainless shelves-

Height: 2160 mm
Volume, gross: 282 lt./242 ltr.
Exterior/Interior: Stainless/Stainless

TECHNICAL INFORMATION

Varenummer	960850411
Category	Dual Temp. Cabinets
Type	Combi Universal/Quick chiller-freezer
Series	GRAM PROCESS
Equipped with	Right hand hinged reversible doors with lock, automatic door closing, 4 stainless shelves
Temperature range I	-25/+10°C (storage)
Temperature range II	-30/+10°C (quick chilling)
Volume, net	228 ltr. / 228 ltr.
Volume, gross	286 ltr. / 286 ltr.
Exterior/Interior	Stainless/Stainless
Dim. W x D x H, mm	820 x 785 x 2125 mm
Weight, packed	136 kg
Insulation	70 mm (cyclopentane)
Refrigerant / GWP	R 290 (propane)/0.20 kg/CO2e 0.65 kg/3
Refrigeration capacity I at -10°C	719 Watt
Refrigeration capacity II at -10°C	389 Watt
Connection	230 V, 50 Hz
Connection load	803 Watt
Please observe	Dual temperature cabinet with 2 compressor systems

