



U/KP 82 CCF L2 4S

Dual temperature cabinet with 2 compressor systems.
Extended temperature range from $-25/+10^{\circ}\text{C}$ (U) in the upper refrigerated section and quick-chill (KP) $-30/+20^{\circ}\text{C}$ in the bottom refrigerated section .

Equipped with: Right hand hinged reversible doors with lock, automatic door closing, 4 stainless shelves-

Height: 2160 mm
Volume, gross: 282 lt./242 ltr.
Exterior/Interior: Stainless/Stainless

TECHNICAL INFORMATION

Varenummer	960850413
Category	Dual Temp. Cabinets
Type	Combi Universal / Quick chill - Remote
Series	GRAM PROCESS
Equipped with	Right hand hinged reversible doors with lock, automatic door closing, 4 stainless shelves
Temperature range I	$-25/+10^{\circ}\text{C}$ (storage)
Temperature range II	$-30/+10^{\circ}\text{C}$ (quick chill)
Volume, net	228 ltr. / 228 ltr.
Volume, gross	286 ltr. / 286 ltr.
Exterior/Interior	Stainless/Stainless
Dim. W x D x H, mm	820 x 785 x 2125
Weight, packed	120 kg
Insulation	70 mm (cyclopentane)
Refrigerant	R 404 A
Refrigeration capacity I at -25°C	300 Watt
Refrigeration capacity II at -25°C	450 Watt
Connection	230 V, 50 Hz
Connection load	202 Watt

