



## ECO PLUS M 70 CCG L2 4N

With an energy consumption of only 328 kWh/year (Energy test Ecodesign) the ECO PLUS M 70 ranks in energy class A.

The Ecodesign test method records the 24 hour energy consumption and multiplies it by 365 to get the annual energy consumption (AEC). The 24 hour consumption is calculated from 2 test periods of 12 hours each. The first period has sequences of door openings while the second is a stabilization period with closed door.

ECO PLUS 70 is the name of one of the new series in the PLUS range. These new cabinets combine stylish design with high functionality and low energy consumption.

- The controls are concealed behind the top panel, protected against splashing water.
- Design principle of "no broken surfaces" makes the cabinets easy to clean.
- The distinctive aluminum profiles stretching from top to bottom on both sides of the cabinet impart strength and enhance appearance.
- The modular rails can go directly in the dishwasher.
- Pedal opener with finesse - read more in the brochure.

ECO PLUS is suitable for the deep 2/1 GN system where 2 pcs. 1/1 GN pans can be placed after each other directly on the support rails.

## TECHNICAL INFORMATION

|                                 |   |
|---------------------------------|---|
| Varenummer                      | 960700111   |
| Category                        | Storage Cabinets  |
| Type                            | Fresh Meat Refrigerator   |
| Line                            | 2/1 GN deep   |
| Series                          | SUPERIOR & ECO PLUS   |
| Equipped with                   | Right hand hinged reversible door, automatic door closing, pedal door opener, 4 grey shelves, LED lighting, dry cooling, rapid thaw |
| Temperature range               | -5/+12°C  |
| Volume, gross                   | 610 ltr.  |
| Net usable volume               | 462 ltr.  |
| Exterior/Interior               | Stainless/Stainless   |
| Dim. W x D x H, mm              | 700 x 905 x 2125  |
| Weight, packed                  | 136 kg  |
| Refrigerant / GWP               | R 600a (isobutane)/0.07 kg/CO2e 0.20 kg/3   |
| Ref.capacity at -10°            | 333 Watt  |
| Connection                      | 230V, 50 Hz   |
| Connection load                 | 248 Watt  |
| Energy Efficiency Class         | A   |
| Energy consumption / year (AEC) | 328 kWh   |
| Sound level                     | Information will follow   |

