

ECO TWIN M 82 LCG L2 4N



With an energy consumption of 344 kWh/year (Energy test Ecodesign) the ECO TWIN M 82 ranks in energy class B according to new EU legislation that was introduced 1st July 2016.

The Ecodesign test method records the 24 hour energy consumption and multiplies it by 365 to get the annual energy consumption (AEC). The 24 hour consumption is calculated from 2 test periods of 12 hours each. The first period has sequences of door openings while the second is a stabilization period with closed door.

These new cabinets combine stylish design with high functionality and low energy consumption.

- The controls are concealed behind the top panel, protected against splashing water.
- Design principle of "no broken surfaces" makes the cabinets easy to clean.
- The distinctive aluminum profiles stretching from top to bottom on both sides of the cabinet impart strength and enhance appearance.
- The modular rails can go directly in the dishwasher
- Pedal opener with finesse - read more in the brochure.

ECO TWIN is suitable for the wide 2/1 GN system where 2 pcs. 1/1 GN pans can be placed side by side on the shelves.

TECHNICAL INFORMATION

| | |
|---------------------------------|--|
| Varenummer | 960820151 |
| Category | Storage Cabinets |
| Type | Fresh Meat Refrigerator |
| Line | 2/1 GN wide |
| Series | SUPERIOR & ECO TWIN |
| Equipped with | Right hand hinged reversible door, automatic door closing, pedal door opener, 4 grey shelves, LED lighting, dry cooling and rapid thaw |
| Temperature range | -5 / +12°C |
| Volume, gross | 614 ltr. |
| Net usable volume | 462 ltr. |
| Exterior/Interior | White/Stainless |
| Dim. W x D x H, mm | 820 x 785 x 2125 |
| Weight, packed | 136 kg |
| Refrigerant / GWP | R600a (isobutane)/0.07 kg/CO ₂ e 0.20 kg/3 |
| Ref.capacity at -10° | 333 Watt |
| Connection | 230 V, 50 Hz |
| Connection load | 248 Watt |
| Energy Efficiency Class | B |
| Energy consumption / year (AEC) | 344 kWh |
| Sound level | 48.1 dB(A) |

